

## ABSTRACT OF THE DISCLOSURE

A method of driving a liquid crystal display that is adaptive for improving a picture quality is provided. In the method, a clock signal is applied to a gate driver. First to third gate output enable signals are applied to the gate driver. A scanning pulse is applied to two gate lines during one period of the clock signal. Accordingly, a desired picture is displayed over a black picture, so that it becomes possible to prevent a motion blur phenomenon. Also, a capacitance value of the liquid crystal cell is fixed, so that a voltage drop amount of the data pulse can be predicted and determined, and the voltage drop amount of the data pulse can be compensated.

1-1  
1-2  
1-3  
1-4  
1-5  
1-6  
1-7  
1-8  
1-9  
1-10  
1-11  
1-12  
1-13  
1-14  
1-15  
1-16  
1-17  
1-18  
1-19  
1-20  
1-21  
1-22  
1-23  
1-24  
1-25  
1-26  
1-27  
1-28  
1-29  
1-30  
1-31  
1-32  
1-33  
1-34  
1-35  
1-36  
1-37  
1-38  
1-39  
1-40  
1-41  
1-42  
1-43  
1-44  
1-45  
1-46  
1-47  
1-48  
1-49  
1-50  
1-51  
1-52  
1-53  
1-54  
1-55  
1-56  
1-57  
1-58  
1-59  
1-60  
1-61  
1-62  
1-63  
1-64  
1-65  
1-66  
1-67  
1-68  
1-69  
1-70  
1-71  
1-72  
1-73  
1-74  
1-75  
1-76  
1-77  
1-78  
1-79  
1-80  
1-81  
1-82  
1-83  
1-84  
1-85  
1-86  
1-87  
1-88  
1-89  
1-90  
1-91  
1-92  
1-93  
1-94  
1-95  
1-96  
1-97  
1-98  
1-99  
1-100